

[Web](#) [Images](#) [Videos](#) [Maps](#) [News](#) [Shopping](#) [Gmail](#) [more](#) ▼
[Sign in](#)

Google scholar

rssi adc gaussian zero mean

Search

[Advanced Scholar Search](#)  
[Scholar Preferences](#)
[Scholar](#) [All articles](#) [Recent articles](#)

Results 1 - 10 of about 347. (0.11 sec)

### [A RSSI-Based Cooperative Anomaly Detection Scheme for Wireless Sensor Networks](#)

Y Tang, P Fan - ... , Networking and Mobile Computing, 2007. WiCom ..., 2007 - [ieeexplore.ieee.org](#)  
 ... **RSSI** output that is sampled by a 10-bit **ADC**. ... where, **RSSI**(d) is the **RSSI** value recorded at distance d ... path loss exponent, and  $X$  is a **Gaussian** random variable ...

[Cited by 3](#) - [Related articles](#) - [All 2 versions](#)

### [Apparatus and Method for Measuring Received Signal Strength Indicator, and Recording ...](#)

Cl Yeh, HS Lim, DS Kwon - US Patent App. 10/588,101, 2004 - Google Patents  
 ... accumulated result; and a computer system estimating an **RSSI** of the ... functions at input and output signals of the **ADC** are approximately **Gaussian** with **zero** ...

[All 4 versions](#)

### [\[PDF\] • Mobility-Assisted Position Estimation in Wireless Sensor Networks](#)

H Chen, P Huang, HC So, K Sezaki - Proceedings of the 2008 14th IEEE International ..., 2008 - [ee.cityu.edu.hk](#)  
 ... which signal decays), and  $\sigma$   $X$  a **zero-mean Gaussian** random vector (in dB) with standard ...  
 This is the **RSSI** signal that has a dedicated **ADC** channel (channel 0 ...

[Related articles](#) - [View as HTML](#) - [All 3 versions](#)

### [Detection of Sybil Attack in Beacon Enabled IEEE802.15.4 Networks- •202.194.20.8 \[PDF\]](#)

F Amini, J Misic, H Pourreza - ... and Mobile Computing Conference, 2008. IWCMC'08. ..., 2008 - [ieeexplore.ieee.org](#)  
 ... standard deviation of the **Gaussian** distribution ... provides a **RSSI** output that is sampled by an 8-bit **ADC**. The **RSSI** is mainly used for RF signals, and the estimate ...

[Related articles](#) - [All 2 versions](#)

### [Self localization of wireless sensor nodes by means of autonomous mobile robots- •unipd.it \[PDF\]](#)

A Zanella, E Menegatti, L Lazzaretto - Proceedings of the 19th Tyrrhenian International ... - Springer  
 ... distribution of this factor is generally assumed to be **Gaussian**, with **zero** ... is converted in digital form by a linear **ADC** with 16 ...  $P_i$  (dBm) = **RSSI** 14 - 114 ...

[Cited by 1](#) - [Related articles](#) - [All 3 versions](#)

### [An integrated baseband processor for universal personalcommunications applications](#)

DE Fague - Third IEEE International Symposium on Personal, ..., 1992 - [ieeexplore.ieee.org](#)  
 ... This circuit digitizes the incoming **RSSI** signal (output from ... savings is achieved by powering the **ADC** for a ... This includes **Gaussian** BbT = 0.5 filters for Digital ...

### [Calibration and Measurement of Signal Strength for Sensor Localization](#)

N Patwari, P Agrawal - Localization Algorithms and Strategies for Wireless ..., 2009 - [books.google.com](#)  
 ... Radio Channel RSSI **RSSI** Circuit **ADC** Pathloss Estimation ... Transmit power battery variations • Receiver **RSSI** circuit device ... to be random, and **Gaussian**, with a ...

[[CITATION](#)] Enhancing Accuracy Performance of Bluetooth Positioning  
LT Son, P Orten - ... and Networking Conference. 2007. WCNC 2007, 2007  
[Related articles](#) - [All 2 versions](#)

[inTrack: High precision tracking of mobile sensor nodes- \\*stanford.edu \[PDF\]](#)  
B Kusy, G Batogh, J Sallai, A Ledeczki, M ... - Lecture Notes in Computer Science, 2007 - Springer  
... as 8 MHz micro- controller, 9 kHz **ADC** sampling, 4 kB ... signal by analyzing the signal  
at the **RSSI** pin of ... distribution of q-ranging errors is not **Gaussian**, but it ...  
[Cited by 14](#) - [Related articles](#) - [BI Direct](#) - [All 12 versions](#)

[A 1.9 GHz fully integrated CMOS DECT transceiver](#)  
AJ Leeuwenburgh, JWF ter Laak, AG Mulders, ... - 2003 IEEE International Solid-State Circuits ..., 2003 - ieeexplore.  
ieee.org  
... In transmit mode, the **Gaussian** shaped input data stream ... A single 8b **ADC** [3] sampling  
at 10.368 ... The received signal strength indicator (**RSSI**) output, computed ...  
[Cited by 3](#) - [Related articles](#) - [All 4 versions](#)

Goooooooooooooogle ►

Result Page:    1   2   3   4   5   6   7   8   9   10    [Next](#)

[Go to Google Home](#) - [About Google](#) - [About Google Scholar](#)

©2009 Google